

What is Claimed is:

1. An optical pickup head which makes a fine movement by a driver, and focuses an incident laser beam to a recording medium for recording/reproducing a data, the optical pickup head comprising:

a micro mirror having at least one 45° mirror surface for reflecting the incident laser beam perpendicular to an incident direction;

a focusing lens under the micro mirror for primary focusing of the laser beam reflected at the micro mirror; and,

an SIL (Solid Immersion Lens) under the focusing lens for secondary focusing of the laser beam focused primarily.

2. An optical pickup head as claimed in claim 1, wherein the 45° mirror surface of the micro mirror has a highly reflective metal coating applied thereto.

3. An optical pickup head as claimed in claim 1, wherein the micro mirror is formed of a silicon substrate.

4. An optical pickup head as claimed in claim 3, wherein the silicon substrate is a 9.74° off-axis (100) silicon wafer.

5. An optical pickup head as claimed in claim 1, wherein the 45° mirror surface of the micro-mirror is formed by anisotropic etching by using one etchant selected from KOH, EDP, TMAH.

09871488-053001
T0050"BBH2860

6. An optical pickup head as claimed in claim 1, wherein the 45° mirror surface of the micro-mirror, a focus plane of the focusing lens, and a focus plane of the SIL are aligned in parallel.

7. An optical pickup head which makes a fine movement by a driver, and focuses an incident laser beam to a recording medium for recording/reproducing a data, the optical pickup head comprising:

a micro mirror having at least one 45° mirror surface for reflecting the incident laser beam perpendicular to an incident direction;

a focusing lens under the micro mirror for primary focusing of the laser beam reflected at the micro mirror;

a first supporting frame fitted under the micro-mirror for supporting the focusing lens;

an SIL (Solid Immersion Lens) under the focusing lens for secondary focusing of the laser beam focused primarily; and,

a second supporting frame fitted under the first supporting frame for supporting the SIL.

8. An optical pickup head as claimed in claim 7, wherein the 45° mirror surface of the micro mirror has a highly reflective metal coating applied thereto.

9. An optical pickup head as claimed in claim 7, wherein the micro mirror is formed of a silicon substrate.

10. An optical pickup head as claimed in claim 9, wherein the silicon substrate is a 9.74° off-axis (100) silicon wafer.

11. An optical pickup head as claimed in claim 7, wherein the 45° mirror surface of the micro-mirror is formed by anisotropic etching by using one etchant selected from KOH, EDP, TMAH.

12. An optical pickup head as claimed in claim 7, wherein the 45° mirror surface of the micro-mirror, a focus plane of the focusing lens, and a focus plane of the SIL are aligned in parallel.

13. An optical pickup head which makes a fine movement by a driver, and focuses an incident laser beam to a recording medium for recording/reproducing a data, the optical pickup head comprising:

a micro mirror having at least one 45° mirror surface for reflecting the incident laser beam perpendicular to an incident direction;

a focusing lens under the micro mirror for primary focusing of the laser beam reflected at the micro mirror;

a first supporting frame fitted under the micro-mirror having an opening in a region for supporting the focusing lens;

an SIL (Solid Immersion Lens) under the focusing lens for secondary focusing of the laser beam focused primarily;

a second supporting frame fitted under the first supporting frame having an opening in a region for supporting the SIL; and,

an air-bearing surface formed under the second supporting frame for making the second supporting frame buoyant.

14. An optical pickup head as claimed in claim 13, wherein the 45° mirror surface of the micro mirror has a highly reflective metal coating applied thereto.

15. An optical pickup head as claimed in claim 13, wherein the micro mirror is formed of a silicon substrate.

16. An optical pickup head as claimed in claim 15, wherein the silicon substrate is a 9.74° off-axis (100) silicon wafer.

17. An optical pickup head as claimed in claim 13, wherein the 45° mirror surface of the micro-mirror is formed by anisotropic etching by using one etchant selected from KOH, EDP, TMAH.

18. An optical pickup head as claimed in claim 13, wherein the 45° mirror surface of the micro-mirror, a focus plane of the focusing lens, and a focus plane of the SIL are aligned in parallel.

19. An optical pickup head as claimed in claim 13, wherein the opening has a side surface sloped at a fixed angle such that an upper width thereof is greater than a lower width thereof.

Sub A27
crit

09871488-053001
T00E50" 88472860

20. An optical pickup head as claimed in claim 13, wherein the SIL is fitted in the opening of the second supporting frame.

Sub 27
Concl

0987148 053001
T00E50" BBT/860